

Dual-Band WiFi 7 Wireless Ceiling AP



DESCRIPTION

The NODEXON NX-AP3600M-C7 is a high-performance Wi-Fi 7 (802.11be) dual-band indoor ceiling-mounted access point designed to deliver fast, stable, and reliable wireless connectivity. It features a 2x2:2SS configuration on both 2.4GHz and 5GHz bands, providing efficient wireless performance for modern high-density indoor environments.

The AP delivers maximum speeds of up to 688Mbps on 2.4GHz and 2882Mbps on 5GHz, with an aggregate throughput of nearly 3600Mbps. Supporting up to 256 concurrent users, the NX-AP3600M-C7 is ideal for offices, hotels, schools, commercial spaces, enterprises, and other demanding indoor networking applications.

FEATURES & BENEFITS

- › WiFi 7 standard, 3600Mbps dual-band wireless rate
- › 2x2 (2.4GHz) + 2x2 (5GHz: 2SS) 4 streams in total
- › Support seamless roaming, high-density deployment, 160MHz bandwidth, 256 devices
- › Support 4096-QAM+MLO+MRU+Preamble Puncture technology
- › 1x2.5G network port + 1xGigabit network port
- › Support PoE (802.3at) power supply and DC power supply, fat and thin in one
- › Support ceiling or wall mounting, simple and easy to operate
- › Support cloud platform/APP operation and maintenance, easy to maintain



3600Mbps



Wireless
Dual-Band



Full Gigabit
Ethernet
Port



PoE/DC
Power
Supply



Fat &
Skinny



Seamless
Roaming



Commercial
Cloud
Platform



Dual-Band WiFi 7
Wireless Ceiling AP



HARDWARE SPECIFICATION

MODEL	NX-AP3600M-C7
Work Frequency	2.4GHz:2.4GHz ~ 2.484GHz 5GHz: 5.150GHz~5.850GHz
WiFi Standard	2.4GHz: 802.11 b /g / n / ax 5GHz: 802.11 a / n / ac / ax
Wireless Speed	2.4GHz provides a maximum access rate of 688Mbps, and 5GHz provides a maximum access rate of 2882Mbps
Device Capacity	256
Tx Power	2.4GHz: <24±2dBm 5GHz: <23±2dBm
Antenna	Built-in omnidirectional antennas
Interface	1×10/100/1000/2500Mbps WAN Port, Support 802.3at input 1×10/100/1000Mbps LAN Port
Reset Button	Reset button (Press and hold 6-10 seconds to restore factory defaults)
Status Indicator	Front-panel tri-color LED (red/green/blue)
Power Supply	DC2.0 12V / 2A, PoE 802.3at
Power Consumption	<20W
Dimensions	186mm×186mm×36.6mm
Work Environment	Working: -10°C to 45°C Storage: -40°C to 70°C Humidity: 5%~95% (Non-Condensing)

ORDER INFORMATION

PART NUMBER	DESCRIPTION
NX-AP3600M-C7	NODEXON Dual-Band WiFi 7 Wireless Ceiling AP

Note:

**Unless TAA compliance is explicitly requested and confirmed per line item prior to order processing, standard commercial (non-TAA) equivalents or general inventory items may be supplied.*

CONNECT WITH US

USA

☎ +1 (877) 677-4040
✉ info@microlinknet.com
📍 1178 Broadway, 3rd
Floor, Suite 318B, New
York, NY 10001

EUROPE

☎ +44 7466717286
✉ uk@microlinknet.com
📍 Fairbourne Drive,
Atterbury,
Buckinghamshire, UK

MIDDLE EAST

☎ +971 44 558570
✉ mena@microlinknet.com
📍 Boulevard Plaza Tower
One, Level 3, Downtown
Dubai, UAE